SDS # 702 Latest Revision: May 2015 Page 1 of 7

Welding Material Sales

SECTION 1: Identification

1.1. Product identifier

Product name: ERCuSi-A

1.2. Details of the supplier of the safety data sheet

Welding Material Sales 1340 Reed Road Geneva, IL 60134 Phone: 630-232-6421

Fax: 888-733-1512

E-mail: info@weldingmaterialsales.com

1.3. Emergency telephone number

Emergency telephone: 800-424-9300

SECTION 2: Hazards identification

2.1. Emergency overview

When this product is used for it's intended purpose fumes and gases produced as a byproduct can be hazardous to your health.

Aggravation of pre-existing respiratory or allergic conditions may occur in some workers. Arc Rays can injure eyes and burn skin. Electric shock can kill.

2.2. Potential Health Effects

2.2.1. Eye

No special hazard risk under normal use. Dusts or particulates may cause mechanical irritation including pain, tearing, and redness. Scratching of the cornea can occur if eye is rubbed. Fumes may be irritating. Contact with the heated material may cause thermal burns.

2.2.2. Skin

SDS # 702 Latest Revision: May 2015 Page 2 of 7 Welding Material Sales

No special hazard risk under normal use. Dusts or particulates may cause mechanical irritation due to abrasion. May cause skin irritation in sensitive individuals. Contact with heated material may cause thermal burns.

2.2.3. Ingestion

Ingestion is an unlikely route of exposure; no hazard in normal industrial use. Swallowing of excessive amounts of the dust may cause irritation, nausea, and diarrhea.

2.2.4. Inhalation

No special hazard risk under normal use. Dusts may cause irritation of the nose, throat, and lungs. Excessive inhalation of metallic fumes and dusts may result in metal fume fever, an influenza-like illness.

2.2.5. Chronic

Respiratory tract irritation, metal fume fever, eye irritation. Long term repeated exposures to excessive fume concentrations may lead to intoxication including kidney disease, anemia, nervous disorders, birth defects and nasal and lung Cancer.

SECTION 3: Composition/Information on Ingredients

3.1. Common name

ERCuSi-A

3.2. Chemical composition

Chemical name	CAS No.	Formula	Composition
Copper	7440-50-8	Cu	bal.
Manganese	7439-96-5	Mn	1.50%
Silicon	7440-21-3	Si	3.40%
Tin	7440-31-5	Sn	1.00%
Zinc	7440-66-6	Zn	1.00%

SECTION 4: First Aid Measures

4.1. Eyes

In case of overexposure to dusts or fumes, immediately flush eyes with plenty of water for at least 15 minutes

SDS # 702 Latest Revision: May 2015 Page 3 of 7

Welding Material Sales

occasionally lifting the eye lids. Get medical attention if irritation persists. Thermal burns should be treated as medical emergencies.

4.2. Skin

In case of overexposure to dusts or particulates, wash with soap and plenty of water. Get medical attention if irritation develops or persists.

4.3. Ingestion

Get medical aid. Do not induce vomiting.

4.4. Inhalation

If inhaled, remove to fresh air. Seek medical attention if symptoms develop.

SECTION 5: Fire Fighting Measures

5.1. General Information

As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. This material is not flammable. However, welding arc and sparks can ignite combustibles. Grinding or other machining operations can produce fine particulatedust that may explode in the presence of a strong ignition source. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

5.2. Extinguishing Media

Never use water as an extinguishing agent around molten or smoldering metal. Water will react violently around any molten metal. Use dry chemical, CO₂ or sand.

SECTION 6: Accidental Release Measure

6.1. General Information

Use proper personal protective equipment as indicated in Section 8.

6.2. Spills/Leaks

Sweep up and place in suitable containers for recycle or disposal. Spilled or released at long industrial condition: Remove ignition sources, Keep away from heat and flame, evacuate area. Avoid breathing dust, vapor, smoke.

SDS # 702 Latest Revision: May 2015 Page 4 of 7

Welding Material Sales

Wear protective equipment. Shut off source of the leak only if it is easy to do so. Keep spilled material out of sewers, ditches and bodies of water.

SECTION 7: Handling and Storage

7.1. Handling

In accordance with good industrial practice, handle with care and avoid unnecessary personal contact. Wash thoroughly after handling. Use with adequate ventilation. Minimize dust generation and accumulation. Do not eat, drink or smoke while handling the product. Keep away from sources of ignition.

7.2. Storage

Keep away from heat and flame. Store in a cool, dry place away from incompatible substances.

SECTION 8: Exposure Controls, Personal Protection

8.1. Engineering Controls

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate ventilation to keep airborne concentrations low.

8.2. Individual Protection for Industrial Use

8.2.1. Eyes

Wear appropriate protective eyeglasses or chemical safety goggles.

8.2.2. Skin

For prolonged or repeated contact use protective gloves.

8.2.3. Clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

8.2.4. Respirators

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or

SDS # 702 Latest Revision: May 2015 Page 5 of 7

Welding Material Sales

other symptoms are experienced.

SECTION 9: Physical and Chemical Properties

9.1. Information on base physical and chemical properties

Physical State : Wire

Color : Red

Odor : Odorless

pH : Not available

Vapor Pressure : Not available

Boiling Point : Not available

Freezing/Melting Point : 995 °F

Autoignition Temperature : Not available
Flash Point : Not applicable
Explosion Limits: Lower : Not applicable
Explosion Limits: Upper : Not applicable
Decomposition Temperature : Not available
Solubility in water : Insoluble
Specific Gravity/Density : 3.5 g/cm³

9.2. Other information

No additional information available.

SECTION 10: Stability and Reactivity

10.1. Chemical Stability

Stable under normal temperatures and pressures.

10.2. Conditions to Avoid

Incompatible materials. Ignition sources, excess heat.

10.3. Incompatibilities with Other Materials

Strong oxidizing agents, mineral acids.

10.4. Hazardous Decomposition Products

Metallic dust or fumes may be produced during welding, burning, grinding and possibly machining.

SDS # 702 Latest Revision: May 2015 Page 6 of 7 Welding Material Sales

10.5. Hazardous Polymerization

Will not occur.

SECTION 11: Toxicological Information

Not including.

SECTION 12: Ecological Information

12.1. Ecotoxicity

Not available

12.2. Other

Do not empty into drains

SECTION 13: Disposal Considerations

Dispose of in a manner consistent with federal, state and local regulations.

SECTION 14: Transport Information

	IATA	IMDG	RID/ADR
Proper shipping name	Not regulated	Not regulated	Not regulated
Hazard class			
Un number			
Packing group			

SECTION 15: Regulatory Information

15.1. Regulatory Information

Reference to the local, national and EU / international regulations.

15.2. Hazard Symbols

Safety Data Sheet SDS # 702 Latest Revision: May 2015 Page 7 of 7 Welding Material Sales

Not available

15.3. Risk Phrases

Not available

15.4. Safety Phrases

S 16 Keep away from sources of ignition.

S 22 Do not breathe dust.

SECTION 16: Other Information

The above information is based on the data of which we are aware and is believed to be correct as of the data hereof. Since this information may be applied under conditions beyond our control and with which may be unfamiliar and since data made available subsequent to the data hereof may suggest modifications of the information,we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.